

## MKT Metall-Kunststoff-Technik GmbH & Co. KG

Auf dem Immel 2 67685 Weilerbach Phone +49 6374 / 9116-0

Internet: http://www.mkt.de email: mkt@mkt.de

## **Report of installation**

Project:		Supervisor:	
-			
Company:		Assembler:	
Construction stage:		Date:	
Type of anchor	Trade name:		
	(e.g. BZ 10-10/90 A4 or		
	VMU-A 10-10/110 + VMU-SH		
	16x100 + VMU 345)		
	Number of Approval:		
Batch Number:	Anchor / Stud		
	Cartridge / Glass Capsule		
Base material	Concrete:	С /	В /
	Masonry:		
	Thickness:		_mm
Drilled hole	Cutting-ø of drill bit:		mm
	Depth of hole:		 mm
	certified drill bit:	🖵 yes 🖵ho	_
	Hammer drilling:	yes <b>D</b> ho	
	Depth stop:	yes 🖵 no	
	Drill hole wet:	yes 🗅 yes	
Cleaning of drilled hole	Method + sequence:		
	Brush-ø:		mm
	Checked with gauge:	🖵 yes 🖵ho	
	Brushed by:	hand	machine
	Blow-out pump:	<b>_</b> 500ml	<b>7</b> 50ml
	Compressed air:		bar
Setting depth	Excess length above surface:		mm
	Interlayer (plaster,screed):		mm
	Setting depth:		_mm
Fixed part	ø of clearance hole:		mm
	Thickness:		_mm
Setting tool	Trade name:		
	Length of spike:		mm
Torque wrench	Туре:		
	Last calibration:		
	Installation torque:		Nm
Dimension of the fixing	Edge distance		
	given in drawing or by engineer:	🖵 yes 🖵ho	
	kept on site:	yes 🖵 ho	
	Spacing between anchors		
	given in drawing or by engineer:	🖵 yes 🖵ho	
	kept on site:	🖵 yes 🖵ho	
Chemical fixings	Date of expiry:		_
	Temperature of cartridge/capsule:		°C
	Temperature of base material:		_°C
	Chemical Capsule installed with hammer drill:		
	Excess mortar at surface:	🖵 yes 🖵ho	
	Time bevor application of installation torque:		_min

Signature supervisor: \_\_\_\_