

# Drywall Plug GKD



### Description

The Drywall Plug GKD is a selfdrilling metal plug with twin cutting tip for fastening into drywall. Suitable for screws of Ø 4 to 4,5 mm and M4.

### Applications

Fixing of switches, curtain rods, wall cupboards, lamps, cable ducts, skirting boards.



**Range of loading: 0,10 - 0,15 kN**

### Drywall Plug GKD



→ Self-drilling plug for drywall

→ Perfect centering tip

Description	Ref. No.	Anchor length mm	Suitable for screws mm	Package content pcs.	Weight per package kg	Content per master box pcs.
GKD 39	37305001	39	Ø 4,0 - 4,5	100	0,68	2400

Loads and performance data		GKD 39	
Mean ultimate loads, drywall d=12,5mm	N <sub>um</sub>	[kN]	0,45
Mean ultimate loads, aerated concrete LC 25/28	N <sub>um</sub>	[kN]	0,40
Mean ultimate loads, gypsum panel	N <sub>um</sub>	[kN]	1,00
Recommended loads, drywall d=12,5mm	rec. N	[kN]	0,10
Recommended loads, aerated concrete LC 25/28	rec. N	[kN]	0,10
Recommended loads, gypsum panel	rec. N	[kN]	0,15

### Installation

