

**VYHLÁSENIE O PARAMETROCH**  
**DoP Nr. MKT-111 - sk**

1. Jedinečný identifikačný kód typu výrobku: **MKT prievlaková kotva BZ plus a BZ-IG**
2. Typ, číslo výrobnej dávky alebo sériové číslo, alebo akýkoľvek iný prvkov umožňujúci identifikáciu stavebného výrobku, ako sa vyžaduje podľa článku 11 ods. 4:

**ETA-99/0010, príloha A3, A5**  
**číslo šarže: vid' obal výrobku**

3. Zamýšľané použitia stavebného výrobku, ktoré uvádza výrobca, v súlade s uplatniteľnou harmonizovanou technickou špecifikáciou:

<b>typ</b>	ocelová expanzná kotva s kontrolovaným uťahovacím momentom (šraubový typ, BZ-IG s vnútorným závitom)
<b>použitie</b>	trhlinový a netrhlinový betón C20/25 - C50/60 (EN 206)
<b>úroveň / kategória</b>	1
<b>zaťaženie</b>	statické alebo kvázi statické, seizmický, kategória C1+C2 (rozmery BZ plus M10, M12, M16, M20)
<b>materiál</b>	<u>pozinkovaná ocel'</u> : len v suchom prostredí v interieri: rozmery: BZ plus: M8, M10, M12, M16, M20, M24, M27 BZ-IG: M6, M8, M10, M12 <u>nehrdzavejúca ocel' (A4)</u> : v interieri alebo exteriéri bez mimoriadnych agresívnych podmienok rozmery: BZ plus: M8, M10, M12, M16, M20, M24 BZ-IG: M6, M8, M10, M12 <u>vysokoodolná nehrdzavejúca ocel' (HCR)</u> : v interieri alebo exteriéri za zvlášť agresívnych podmienok rozmery: BZ plus: M8, M10, M12, M16, M20, M24 BZ-IG: M6, M8, M10, M12
<b>teplotný rozsah (ak je to relevantné)</b>	--

4. Meno, registrované obchodné meno alebo registrovaná ochranná známka a kontaktná adresa výrobcu, ako sa vyžaduje podľa článku 11 ods. 5:

**MKT Metall-Kunststoff-Technik GmbH & Co. KG**  
**Auf dem Immel 2**  
**D - 67685 Weilerbach**

5. V prípade potreby meno a kontaktná adresa splnomocneného zástupcu, ktorého splnomocnenie zahŕňa úlohy vymedzené v článku 12 ods. 2: --
6. Systém alebo systémy posudzovania a overovania nemennosti parametrov stavebného výrobku, ako sa uvádzajú v prílohe V: **Systéme 1**
7. V prípade vyhlásenia o parametroch týkajúceho sa stavebného výrobku, na ktorý sa vzťahuje harmonizovaná norma:

--

8. V prípade vyhlásenia o parametroch týkajúceho sa stavebného výrobku, na ktorý bolo vypracované európske technické posúdenie:

**Nemecký inštitút pre stavebnú techniku, Berlín**

vydal:

**ETA-99/0010**

na základe:

**ETAG 001-2**

vykonala notifikovaná osoba na certifikáciu výrobkov 1343-CPR v systéme: 1

- i) určenie typu výrobku na základe typovej skúšky (vrátane odberu vzoriek), typového výpočtu, tabuľkových hodnôt alebo opisnej dokumentácie výrobku;
- ii) počiatocnej inšpekcie výrobného závodu a systému riadenia výroby;
- iii) priebežného dohľadu nad systémom riadenia výroby a posudzovania a hodnotenia systému riadenia výroby.

a vydala: prehlásenie o zhode 1343-CPR-M 550-1

9. Deklarované parametre:

podstatné vlastnosti	návrhová metóda	prevedenie		harmonizovaná technická špecifikácia
		BZ plus	BZ-IG	
charakteristická únosnosť pri zaťažení v ľahu	ETAG 001, príloha C CEN/TS 1992-4	ETA-99/0010, príloha C1-C4	ETA-99/0010, príloha C10-C11	ETAG 001
charakteristická únosnosť pri zaťažení v šmyku	ETAG 001, príloha C CEN/TS 1992-4	ETA-99/0010, príloha C5	ETA-99/0010, príloha C12	
Charakteristický odpor pri seismické zaťaženiu	TR 045	ETA-99/0010, príloha C6	NPD	
Shift v prevádzke	ETAG 001, príloha C CEN/TS 1992-4	ETA-99/0010, príloha C8-C9	ETA-99/0010, príloha C14	
charakteristická únosnosť pri požiare	TR 020 CEN/TS 1992-4	ETA-99/0010, príloha C7	ETA-99/0010, príloha C13	

Ak sa použila špecifická technická dokumentácia podľa článkov 37 alebo 38, požiadavky, ktoré výrobok splňa:  
--

10. Parametre výrobku uvedené v bodech 1 a 2 sú v zhode s deklarovanými parametrami v bode 9. Toto vyhlásenie o parametroch sa vydáva na výhradnú zodpovednosť výrobcu uvedeného v bode 4.

Podpísal za a v mene výrobcu:

*L. Weustenhagen*  
Lore Weustenhagen  
(vedúci podniku)  
Weilerbach, 09.01.2015

i.V. *Detlef Bigalke*  
Dipl.-Ing. Detlef Bigalke  
(riadič vývoja produktov)



**Table C1:** Characteristic values for **tension loads**, BZ plus **zinc plated, cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

Anchor size		M8	M10	M12	M16	M20	M24	M27
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[ $\cdot$ ]				1,0		
<b>Steel failure</b>								
Characteristic tension resistance	$N_{Rk,s}$	[kN]	16	27	40	60	86	126
Partial safety factor	$\gamma_{Ms}$	[ $\cdot$ ]	1,53		1,5	1,6		1,5
<b>Pull-out</b>								
<b>Standard anchorage depth</b>								
Characteristic resistance in concrete C20/25	$N_{Rk,p}$	[kN]	5	9	16	25	1)	1)
<b>Reduced anchorage depth</b>								
Characteristic resistance in concrete C20/25	$N_{Rk,p,red}$	[kN]	5	7,5	1)	1)		
Increasing factor for $N_{Rk,p}$ and $N_{Rk,p,red}$	$\psi_c$	[ $\cdot$ ]			$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$			
<b>Concrete cone failure</b>								
Effective anchorage depth	$h_{ref}$	[mm]	46	60	70	85	100	115
Reduced anchorage depth	$h_{ref,red}$	[mm]	35 <sup>2)</sup>	40	50	65		
Factor for cracked concrete	$k_{cr}$	[ $\cdot$ ]				7,2		

<sup>1)</sup> Pull-out is not decisive.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

### Wedge Anchor BZ plus

#### Performance

Characteristic values for **tension loads**, BZ plus **zinc plated cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

#### Annex C1

**Table C2:** Characteristic values for **tension loads**, BZ plus A4 / HCR, **cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

Anchor size		M8	M10	M12	M16	M20	M24
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[ $-$ ]				1,0	
<b>Steel failure</b>							
Characteristic tension resistance	$N_{Rk,s}$	[kN]	16	27	40	64	108
Partial safety factor	$\gamma_{Ms}$	[ $-$ ]		1,5		1,68	1,5
<b>Pull-out</b>							
<b>Standard anchorage depth</b>							
Characteristic resistance in concrete C20/25	$N_{Rk,p}$	[kN]	5	9	16	25	1) 40
<b>Reduced anchorage depth</b>							
Characteristic resistance in concrete C20/25	$N_{Rk,p,red}$	[kN]	5	7,5	1) 1)		
Increasing factor for $N_{Rk,p}$ and $N_{Rk,p,red}$	$\psi_c$	[ $-$ ]			$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$		
<b>Concrete cone failure</b>							
Effective anchorage depth	$h_{ef}$	[mm]	46	60	70	85	100
Reduced anchorage depth	$h_{ef,red}$	[mm]	35 <sup>2)</sup>	40	50	65	
Factor for cracked concrete	$k_{cr}$	[ $-$ ]				7,2	

1) Pull-out is not decisive.

2) Use restricted to anchoring of structural components statically indeterminate.

### Wedge Anchor BZ plus

#### Performance

Characteristic values for **tension loads**, BZ plus A4 / HCR, **cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

#### Annex C2

**Table C3: Characteristic values for tension loads, BZ plus zinc plated, non-cracked concrete, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4**

Anchor size	M8	M10	M12	M16	M20	M24	M27
Installation safety factor $\gamma_2 = \gamma_{\text{inst}}$ [-]					1,0		
<b>Steel failure</b>							
Characteristic tension resistance $N_{Rk,s}$ [kN]	16	27	40	60	86	126	196
Partial safety factor $\gamma_{Ms}$ [-]		1,53		1,5		1,6	1,5
<b>Pull-out</b>							
<b>Standard anchorage depth</b>							
Characteristic resistance in non-cracked concrete C20/25 $N_{Rk,p}$ [kN]	12	16	25	35	1)	1)	1)
<b>Reduced anchorage depth</b>							
Characteristic resistance in non-cracked concrete C20/25 $N_{Rk,p,\text{red}}$ [kN]	7,5	9	1)	1)			
Splitting For the proof against splitting failure $N^0_{Rk,c}$ has to be replaced by $N^0_{Rk,sp}$ with consideration of the member thickness							
<b>Standard anchorage depth</b>							
Splitting for standard thickness of concrete member (The higher resistance of case 1 and case 2 may be applied; the values $s_{cr,sp}$ and $c_{cr,sp}$ may be linearly interpolated for the member thickness $h_{\min} < h < h_{\text{std}}$ (Case 2); $\psi_{h,sp}=1,0$ )							
Standard thickness of concrete $h_{\min,1} \geq$ [mm]	100	120	140	170	200	230	250
<b>Case 1</b>							
Characteristic resistance in non-cracked concrete C20/25 $N^0_{Rk,sp}$ [kN]	9	12	20	30	40	1)	50
Spacing (edge distance) $s_{cr,sp} (= 2 c_{cr,sp})$ [mm]				3 $h_{\text{ef}}$			
<b>Case 2</b>							
Characteristic resistance in non-cracked concrete C20/25 $N^0_{Rk,sp}$ [kN]	12	16	25	35	1)	1)	1)
Spacing (edge distance) $s_{cr,sp} (= 2 c_{cr,sp})$ [mm]			4 $h_{\text{ef}}$		4,4 $h_{\text{ef}}$	3 $h_{\text{ef}}$	5 $h_{\text{ef}}$
Splitting for minimum thickness of concrete member							
Minimum thickness of concrete $h_{\min,2} \geq$ [mm]	80	100	120	140			
Characteristic resistance in non-cracked concrete C20/25 $N^0_{Rk,sp}$ [kN]	12	16	25	35			
Spacing (edge distance) $s_{cr,sp} (= 2 c_{cr,sp})$ [mm]			5 $h_{\text{ef}}$				
<b>Reduced anchorage depth</b>							
Minimum thickness of concrete $h_{\min,3} \geq$ [mm]	80	80	100	140			
Characteristic resistance in non-cracked concrete C20/25 $N^0_{Rk,sp}$ [kN]	7,5	9	1)	1)			
Spacing (edge distance) $s_{cr,sp} (= 2 c_{cr,sp})$ [mm]	200	200	250	300			
Increasing factor for $N_{Rk,p(\text{red})}$ and $N^0_{Rk,sp}$ $\psi_c$ [-]					$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$		
<b>Concrete cone failure</b>							
Effective anchorage depth $h_{\text{ef}}$ [mm]	46	60	70	85	100	115	125
Reduced anchorage depth $h_{\text{ef},\text{red}}$ [mm]	35 <sup>2)</sup>	40	50	65			
Factor for non-cracked concrete $k_{ucr}$ [-]				10,1			

<sup>1)</sup> Pull-out is not decisive.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

### Wedge Anchor BZ plus

#### Performance

Characteristic values for **tension loads**, BZ plus **zinc plated, non-cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

#### Annex C3

**Table C4:** Characteristic values for **tension loads**, BZ plus A4 / HCR, **non-cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

Anchor size		M8	M10	M12	M16	M20	M24
Installation safety factor	$\gamma_2 = \gamma_{\text{inst}}$	[ - ]			1,0		
<b>Steel failure</b>							
Characteristic tension resistance	$N_{Rk,s}$	[kN]	16	27	40	64	108
Partial safety factor	$\gamma_{Ms}$	[ - ]		1,5		1,68	1,5
<b>Pull-out</b>							
<b>Standard anchorage depth</b>							
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,p}$	[kN]	12	16	25	35	1)
<b>Reduced anchorage depth</b>							
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,p,\text{red}}$	[kN]	7,5	9	1)	1)	
<b>Splitting</b> For the proof against splitting failure $N^0_{Rk,c}$ has to be replaced by $N^0_{Rk,sp}$ with consideration of the member thickness							
<b>Standard anchorage depth</b>							
Splitting for <b>standard thickness of concrete member</b> (The higher resistance of case 1 and case 2 may be applied; the values $s_{cr,sp}$ and $c_{cr,sp}$ may be linearly interpolated for the member thickness $h_{min} < h < h_{std}$ (Case 2); $\psi_{h,sp} = 1,0$ )							
Standard thickness of concrete	$h_{min,1} \geq$	[mm]	100	120	140	160	200
<b>Case 1</b>							
Characteristic resistance in non-cracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	9	12	20	30	40
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]			3 $h_{ef}$		
<b>Case 2</b>							
Characteristic resistance in non-cracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	12	16	25	35	1)
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]	230	250	280	400	440
Splitting for <b>minimum thickness of concrete member</b>							
Minimum thickness of concrete	$h_{min,2} \geq$	[mm]	80	100	120	140	
Characteristic resistance in non-cracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	12	16	25	35	
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]			5 $h_{ef}$		
<b>Reduced anchorage depth</b>							
Minimum thickness of concrete	$h_{min,3} \geq$	[mm]	80	80	100	140	
Characteristic resistance in non-cracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	7,5	9	1)	1)	
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]	200	200	250	300	
Increasing factor for $N_{Rk,p(\text{red})}$ and $N^0_{Rk,sp}$	$\psi_c$	[ - ]			$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$		
<b>Concrete cone failure</b>							
Effective anchorage depth	$h_{ef}$	[mm]	46	60	70	85	100
Reduced anchorage depth	$h_{ef,\text{red}}$	[mm]	35 <sup>2)</sup>	40	50	65	
Factor for non-cracked concrete	$k_{ucr}$	[ - ]			10,1		

<sup>1)</sup> Pull-out is not decisive.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

### Wedge Anchor BZ plus

#### Performance

Characteristic values for **tension loads**, BZ plus A4 / HCR, **non-cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

#### Annex C4

**Table C5:** Characteristic values for **shear loads**, BZ plus,  
**cracked and non-cracked concrete**, static or quasi static action,  
design method A according to ETAG 001, Annex C or CEN/TS 1992-4

Anchor size		M8	M10	M12	M16	M20	M24	M27	
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[ $\cdot$ ]				1,0			
<b>Steel failure without lever arm, Steel zinc plated</b>									
Characteristic shear resistance	$V_{Rk,s}$ [kN]	12,2	20,1	30	55	69	114	169,4	
Factor for ductility	$k_2$	[ $\cdot$ ]				1,0			
Partial safety factor	$\gamma_{Ms}$	[ $\cdot$ ]		1,25		1,33	1,25	1,25	
<b>Steel failure without lever arm, Stainless steel A4, HCR</b>									
Characteristic shear resistance	$V_{Rk,s}$ [kN]	13	20	30	55	86	123,6		
Factor for ductility	$k_2$	[ $\cdot$ ]				1,0			
Partial safety factor	$\gamma_{Ms}$	[ $\cdot$ ]		1,25		1,4	1,25		
<b>Steel failure with lever arm, Steel zinc plated</b>									
Characteristic bending resistance	$M^0_{Rk,s}$ [Nm]	23	47	82	216	363	898	1331,5	
Partial safety factor	$\gamma_{Ms}$	[ $\cdot$ ]		1,25		1,33	1,25	1,25	
<b>Steel failure with lever arm, Stainless steel A4, HCR</b>									
Characteristic bending resistance	$M^0_{Rk,s}$ [Nm]	26	52	92	200	454	785,4		
Partial safety factor	$\gamma_{Ms}$	[ $\cdot$ ]		1,25		1,4	1,25		
<b>Concrete pry-out failure</b>									
k factor	$k_{(3)}$	[ $\cdot$ ]		2,4			2,8		
<b>Concrete edge failure</b>									
Effective length of anchor in shear loading with $h_{ef}$	Steel zinc plated Stainless steel A4, HCR	$l_f$ [mm]	46	60	70	85	100	115	125
Effective length of anchor in shear loading with $h_{ef,red}$	Steel zinc plated Stainless steel A4, HCR	$l_{f,red}$ [mm]	35	40	50	65			
Outside diameter of anchor	$d_{nom}$	[mm]	8	10	12	16	20	24	27

### Wedge Anchor BZ plus

#### Performance

Characteristic values for **shear loads**, BZ plus,  
**cracked and non-cracked concrete**, static or quasi static action,  
design method A according to ETAG 001, Annex C or CEN/TS 1992-4

#### Annex C5

**Table C6:** Characteristic resistance for **seismic loading**, BZ plus, **standard anchorage depth**, performance category **C1** and **C2**, design according to TR045

<b>Tension loads</b>					
<b>Anchor size</b>		<b>M10</b>	<b>M12</b>	<b>M16</b>	<b>M20</b>
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]			
<b>Steel failure, steel zinc plated</b>					
Characteristic resistance <b>C1</b>	$N_{Rk,s,seis,C1}$	[kN]	27	40	60
Characteristic resistance <b>C2</b>	$N_{Rk,s,seis,C2}$	[kN]	27	40	60
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,53	1,5	1,6
<b>Steel failure, stainless steel A4, HCR</b>					
Characteristic resistance <b>C1</b>	$N_{Rk,s,seis,C1}$	[kN]	27	40	64
Characteristic resistance <b>C2</b>	$N_{Rk,s,seis,C2}$	[kN]	27	40	64
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,5		1,68
<b>Pull-out</b>					
Characteristic resistance <b>C1</b>	$N_{Rk,p,seis,C1}$	[kN]	9	16	25
Characteristic resistance <b>C2</b>	$N_{Rk,p,seis,C2}$	[kN]	3,6	10,2	13,8
<b>Shear loads</b>					
<b>Steel failure without lever arm, Steel zinc plated</b>					
Characteristic resistance <b>C1</b>	$V_{Rk,s,seis,C1}$	[kN]	20	27	44
Characteristic resistance <b>C2</b>	$V_{Rk,s,seis,C2}$	[kN]	14	16,2	35,7
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,25		1,33
<b>Steel failure without lever arm, Stainless steel A4, HCR</b>					
Characteristic resistance <b>C1</b>	$V_{Rk,s,seis,C1}$	[kN]	20	27	44
Characteristic resistance <b>C2</b>	$V_{Rk,s,seis,C2}$	[kN]	14	16,2	35,7
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,25		1,4

### Wedge Anchor BZ plus

#### Performance

Characteristic resistance for **seismic loading**, BZ plus, **standard anchorage depth**, performance category **C1** and **C2**, design according to TR045

#### Annex C6

**Table C7:** Characteristic values for tension and shear load under fire exposure, BZ plus, standard anchorage depth, cracked and non-cracked concrete C20/25 to C50/60, design acc. to TR 020 or CEN/TS 1992-4, Annex D

Anchor size		M8	M10	M12	M16	M20	M24	M27	
<b>Tension load</b>									
<b>Steel failure</b>									
<b>Steel zinc plated</b>									
Characteristic resistance	R30	N <sub>Rk,s,fi</sub> [kN]	1,4	2,2	3,2	6,0	9,4	13,6	
	R60		1,1	1,8	2,8	5,2	8,2	11,8	
	R90		0,8	1,4	2,4	4,4	6,9	10,0	
	R120		0,7	1,2	2,2	4,0	6,3	9,1	
<b>Stainless steel A4, HCR</b>									
Characteristic resistance	R30	V <sub>Rk,s,fi</sub> [kN]	3,8	6,9	11,5	21,5	33,5	48,2	
	R60		2,9	5,2	8,6	16	25,0	35,9	
	R90		2,0	3,5	5,6	10,5	16,4	23,6	
	R120		1,6	2,7	4,2	7,8	12,1	17,4	
<b>Shear load</b>									
<b>Steel failure without lever arm</b>									
<b>Steel zinc plated</b>									
Characteristic resistance	R30	M <sup>0</sup> <sub>Rk,s,fi</sub> [Nm]	1,6	2,6	3,8	7,0	11	16	
	R60		1,5	2,5	3,6	6,8	11	15	
	R90		1,2	2,1	3,5	6,5	10	15	
	R120		1,0	2,0	3,4	6,4	10	14	
<b>Stainless steel A4, HCR</b>									
Characteristic resistance	R30	V <sub>Rk,s,fi</sub> [kN]	3,8	6,9	11,5	21,5	33,5	48,2	
	R60		2,9	5,2	8,6	16	25,0	35,9	
	R90		2,0	3,5	5,6	10,5	16,4	23,6	
	R120		1,6	2,7	4,2	7,8	12,1	17,4	
<b>Steel failure with lever arm</b>									
<b>Steel zinc plated</b>									
Characteristic resistance	R30	M <sup>0</sup> <sub>Rk,s,fi</sub> [Nm]	1,7	3,3	5,9	15	29	50	
	R60		1,6	3,2	5,6	14	28	48	
	R90		1,2	2,7	5,4	14	27	47	
	R120		1,1	2,5	5,3	13	26	46	
<b>Stainless steel A4, HCR</b>									
Characteristic resistance	R30	M <sup>0</sup> <sub>Rk,s,fi</sub> [Nm]	3,8	9,0	17,9	45,5	88,8	153,5	
	R60		2,9	6,8	13,3	33,9	66,1	114,3	
	R90		2,1	4,5	8,8	22,2	43,4	75,1	
	R120		1,6	3,4	6,5	16,4	32,1	55,5	

The characteristic resistance for pull-out failure, concrete cone failure, concrete pry-out and concrete edge failure can be calculated according to TR020 / CEN/TS 1992-4. If pull-out is not decisive N<sub>Rk,p</sub> in Eq. 2.4 and Eq. 2.5, TR 020 must be replaced by N<sup>0</sup><sub>Rk,c</sub>.

### Wedge Anchor BZ plus

#### Performance

Characteristic values for tension and shear load under fire exposure, BZ plus, standard anchorage depth, cracked and non-cracked concrete C20/25 to C50/60, design acc. to TR 020 or CEN/TS 1992-4, Annex D

#### Annex C7

**Table C8: Displacements under tension load, BZ plus**

Anchor size		M8	M10	M12	M16	M20	M24	M27
<b>Standard anchorage depth</b>								
<b>Steel zinc plated</b>								
Tension load in cracked concrete	N	[kN]	2,4	4,3	7,6	11,9	17,1	21,1
Displacement	$\delta_{N0}$	[mm]	0,6	1,0	0,4	1,0	0,9	0,7
	$\delta_{N\infty}$	[mm]	1,4	1,2	1,4	1,3	1,0	1,2
Tension load in non-cracked concrete	N	[kN]	5,7	7,6	11,9	16,7	23,8	29,6
Displacement	$\delta_{N0}$	[mm]	0,4	0,5	0,7	0,3	0,4	0,5
	$\delta_{N\infty}$	[mm]		0,8	1,4		0,8	1,4
<b>Displacements under seismic tension loads C2</b>								
Displacements for DLS	$\delta_{N,\text{seis},C2(\text{DLS})}$	[mm]		4,1	4,9	3,6	5,1	
Displacements for ULS	$\delta_{N,\text{seis},C2(\text{ULS})}$	[mm]		13,8	15,7	9,5	15,2	
<b>Stainless steel A4, HCR</b>								
Tension load in cracked concrete	N	[kN]	2,4	4,3	7,6	11,9	17,1	19,0
Displacement	$\delta_{N0}$	[mm]	0,7	1,8	0,4	0,7	0,9	0,5
	$\delta_{N\infty}$	[mm]	1,2	1,4	1,4	1,4	1,0	1,8
Tension load in non-cracked concrete	N	[kN]	5,8	7,6	11,9	16,7	23,8	33,5
Displacement	$\delta_{N0}$	[mm]	0,6	0,5	0,7	0,2	0,4	0,5
	$\delta_{N\infty}$	[mm]	1,2	1,0	1,4	0,4	0,8	1,1
<b>Displacements under seismic tension loads C2</b>								
Displacements for DLS	$\delta_{N,\text{seis},C2(\text{DLS})}$	[mm]		4,1	4,9	3,6	5,1	
Displacements for ULS	$\delta_{N,\text{seis},C2(\text{ULS})}$	[mm]		13,8	15,7	9,5	15,2	
<b>Reduced anchorage depth</b>								
Tension load in cracked concrete	N	[kN]	2,4	3,6	6,1	9,0		
Displacement	$\delta_{N0}$	[mm]	0,8	0,7	0,5	1,0		
	$\delta_{N\infty}$	[mm]	1,2	1,0	0,8	1,1		
Tension load in non-cracked concrete	N	[kN]	3,7	4,3	8,5	12,6		
Displacement	$\delta_{N0}$	[mm]	0,1	0,2	0,2	0,2		
	$\delta_{N\infty}$	[mm]	0,7	0,7	0,7	0,7		

#### **Wedge Anchor BZ plus**

**Performance**  
Displacements under tension load

**Annex C8**

**Table C9: Displacements under shear load, BZ plus**

Anchor size	M8	M10	M12	M16	M20	M24	M27		
<b>Standard anchorage depth</b>									
<b>Steel zinc plated</b>									
Shear load in cracked and non-cracked concrete	V	[kN]	6,9	11,4	17,1	31,4	36,8	64,9	96,8
Displacement	$\delta_{V0}$	[mm]	2,0	3,2	3,6	3,5	1,8	3,5	3,6
	$\delta_{V\infty}$	[mm]	3,0	4,7	5,5	5,3	2,7	5,3	5,4
<b>Displacements under seismic shear loads C2</b>									
Displacements for DLS	$\delta_{V,\text{seis},C2(\text{DLS})}$	[mm]		2,7	3,5	4,3	4,7		
Displacements for ULS	$\delta_{V,\text{seis},C2(\text{ULS})}$	[mm]		5,3	9,5	9,6	10,1		
<b>Stainless steel A4, HCR</b>									
Shear load in cracked and non-cracked concrete	V	[kN]	7,3	11,4	17,1	31,4	43,8	70,6	
Displacement	$\delta_{V0}$	[mm]	1,9	2,4	4,0	4,3	2,9	2,8	
	$\delta_{V\infty}$	[mm]	2,9	3,6	5,9	6,4	4,3	4,2	
<b>Displacements under seismic shear loads C2</b>									
Displacements for DLS	$\delta_{V,\text{seis},C2(\text{DLS})}$	[mm]		2,7	3,5	4,3	4,7		
Displacements for ULS	$\delta_{V,\text{seis},C2(\text{ULS})}$	[mm]		5,3	9,5	9,6	10,1		
<b>Reduced anchorage depth</b>									
<b>Steel zinc plated</b>									
Shear load in cracked and non-cracked concrete	V	[kN]	6,9	11,4	17,1	31,4			
Displacement	$\delta_{V0}$	[mm]	2,0	3,2	3,6	3,5			
	$\delta_{V\infty}$	[mm]	3,0	4,7	5,5	5,3			
<b>Stainless steel A4, HCR</b>									
Shear load in cracked and non-cracked concrete	V	[kN]	7,3	11,4	17,1	31,4			
Displacement	$\delta_{V0}$	[mm]	1,9	2,4	4,0	4,3			
	$\delta_{V\infty}$	[mm]	2,9	3,6	5,9	6,4			

**Wedge Anchor BZ plus**

**Performance**  
Displacements under shear load

**Annex C9**

**Table C10:** Characteristic values for **tension loads, BZ-IG, cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

Anchor size		M6	M8	M10	M12
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,2		
<b>Steel failure</b>					
Characteristic tension resistance, steel zinc plated	$N_{Rk,s}$	[kN]	16,1	22,6	26,0
Partial safety factor	$\gamma_{Ms}$	[-]		1,5	
Characteristic tension resistance, stainless steel A4, HCR	$N_{Rk,s}$	[kN]	14,1	25,6	35,8
Partial safety factor	$\gamma_{Ms}$	[-]		1,87	
<b>Pull-out failure</b>					
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p}$	[kN]	5	9	12
Increasing factor	$\psi_c$	[-]		$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$	
<b>Concrete cone failure</b>					
Effective anchorage depth	$h_{ref}$	[mm]	45	58	65
Factor for cracked concrete	$k_{cr}$	[-]		7,2	

### Wedge Anchor BZ-IG

#### Performance

Characteristic values for **tension loads, BZ-IG, cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

**Annex C10**

**Table C11:** Characteristic values for **tension loads, BZ-IG, non-cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

Anchor size		M6	M8	M10	M12
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[ - ]		1,2	
<b>Steel failure</b>					
Characteristic tension resistance, steel zinc plated	$N_{Rk,s}$	[kN]	16,1	22,6	26,0
Partial safety factor	$\gamma_{Ms}$	[ - ]		1,5	
Characteristic tension resistance, stainless steel A4, HCR	$N_{Rk,s}$	[kN]	14,1	25,6	35,8
Partial safety factor	$\gamma_{Ms}$	[ - ]		1,87	
<b>Pull-out</b>					
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,p}$	[kN]	12	16	20
<b>Splitting</b> ( $N^0_{Rk,c}$ has to be replaced by $N^0_{Rk,sp}$ . The higher resistance of Case 1 and Case 2 may be applied.)					
Minimum thickness of concrete member	$h_{min}$	[mm]	100	120	130
<b>Case 1</b>					
Characteristic resistance in non-cracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	9	12	16
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]		3 $h_{ef}$	
<b>Case 2</b>					
Characteristic resistance in non-cracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	12	16	20
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]		5 $h_{ef}$	
Increasing factor for $N_{Rk,p}$ and $N^0_{Rk,sp}$	$\psi_c$	[ - ]		$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$	
<b>Concrete cone failure</b>					
Effective anchorage depth	$h_{ef}$	[mm]	45	58	65
Factor for non-cracked concrete	$K_{ucr}$	[ - ]		10,1	

### Wedge Anchor BZ-IG

#### Performance

Characteristic values for **tension loads, BZ-IG, non-cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

**Annex C11**

**Table C12:** Characteristic values for **shear loads, BZ-IG, cracked and non-cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

Anchor size		M6	M8	M10	M12
Installation safety factor	$\gamma_2 = \gamma_{\text{inst}}$	[ $\gamma$ ]		1,0	
<b>BZ-IG, steel zinc plated</b>					
<b>Steel failure without lever arm, Installation type V</b>					
Characteristic shear resistance	$V_{Rk,s}$	[kN]	5,8	6,9	10,4
					25,8
<b>Steel failure without lever arm, Installation type D</b>					
Characteristic shear resistance	$V_{Rk,s}$	[kN]	5,1	7,6	10,8
					24,3
<b>Steel failure with lever arm, Installation type V</b>					
Characteristic bending resistance	$M_{Rk,s}^0$	[Nm]	12,2	30,0	59,8
					104,6
<b>Steel failure with lever arm, Installation type D</b>					
Characteristic bending resistance	$M_{Rk,s}^0$	[Nm]	36,0	53,2	76,0
					207
Partial safety factor for $V_{Rk,s}$ and $M_{Rk,s}^0$	$\gamma_{Ms}$	[ $\gamma$ ]		1,25	
Factor of ductility	$k_2$	[ $\gamma$ ]		1,0	
<b>BZ-IG, stainless steel A4, HCR</b>					
<b>Steel failure without lever arm, Installation type V</b>					
Characteristic shear resistance	$V_{Rk,s}$	[kN]	5,7	9,2	10,6
					23,6
Partial safety factor	$\gamma_{Ms}$	[ $\gamma$ ]		1,25	
<b>Steel failure without lever arm, Installation type D</b>					
Characteristic shear resistance	$V_{Rk,s}$	[kN]	7,3	7,6	9,7
					29,6
Partial safety factor	$\gamma_{Ms}$	[ $\gamma$ ]		1,25	
<b>Steel failure with lever arm, Installation type V</b>					
Characteristic bending resistance	$M_{Rk,s}^0$	[Nm]	10,7	26,2	52,3
					91,6
Partial safety factor	$\gamma_{Ms}$	[ $\gamma$ ]		1,56	
<b>Steel failure with lever arm, Installation type D</b>					
Characteristic bending resistance	$M_{Rk,s}^0$	[Nm]	28,2	44,3	69,9
					191,2
Partial safety factor	$\gamma_{Ms}$	[ $\gamma$ ]		1,25	
Factor of ductility	$k_2$	[ $\gamma$ ]		1,0	
<b>Concrete pry-out failure</b>					
K factor	$k_{(3)}$	[ $\gamma$ ]	1,5	1,5	2,0
					2,0
<b>Concrete edge failure</b>					
Effective length of anchor in shear loading	$l_f$	[mm]	45	58	65
					80
Effective diameter of anchor	$d_{\text{nom}}$	[mm]	8	10	12
					16

### Wedge Anchor BZ-IG

#### Performance

Characteristic values for **shear loads, BZ-IG, cracked and non-cracked concrete**, static and quasi-static action, design method A according to ETAG 001, Annex C or CEN/TS 1992-4

**Annex C12**

**Table C13: Characteristic values for tension and shear load under fire exposure, BZ-IG**  
 cracked and non-cracked concrete C20/25 to C50/60,  
 design acc. to TR 020 or CEN/TS 1992-4, Annex D

Anchor size		M6	M8	M10	M12	
<b>Tension load</b>						
<b>Steel failure</b>						
<b>Steel zinc plated</b>						
Characteristic resistance	R30	N <sub>Rk,s,fi</sub> [kN]	0,7	1,4	2,5	3,7
	R60		0,6	1,2	2,0	2,9
	R90		0,5	0,9	1,5	2,2
	R120		0,4	0,8	1,3	1,8
<b>Stainless steel A4, HCR</b>						
Characteristic resistance	R30	V <sub>Rk,s,fi</sub> [kN]	2,9	5,4	8,7	12,6
	R60		1,9	3,8	6,3	9,2
	R90		1,0	2,1	3,9	5,7
	R120		0,5	1,3	2,7	4,0
<b>Shear load</b>						
<b>Steel failure without lever arm</b>						
<b>Steel zinc plated</b>						
Characteristic resistance	R30	M <sup>0</sup> <sub>Rk,s,fi</sub> [Nm]	0,7	1,4	2,5	3,7
	R60		0,6	1,2	2,0	2,9
	R90		0,5	0,9	1,5	2,2
	R120		0,4	0,8	1,3	1,8
<b>Stainless steel A4, HCR</b>						
Characteristic resistance	R30	V <sub>Rk,s,fi</sub> [kN]	2,9	5,4	8,7	12,6
	R60		1,9	3,8	6,3	9,2
	R90		1,0	2,1	3,9	5,7
	R120		0,5	1,3	2,7	4,0
<b>Steel failure with lever arm</b>						
<b>Steel zinc plated</b>						
Characteristic resistance	R30	M <sup>0</sup> <sub>Rk,s,fi</sub> [Nm]	0,5	1,4	3,3	5,7
	R60		0,4	1,2	2,6	4,6
	R90		0,4	0,9	2,0	3,4
	R120		0,3	0,8	1,6	2,8
<b>Stainless steel A4, HCR</b>						
Characteristic resistance	R30	M <sup>0</sup> <sub>Rk,s,fi</sub> [Nm]	2,2	5,5	11,2	19,6
	R60		1,5	3,9	8,1	14,3
	R90		0,7	2,2	5,1	8,9
	R120		0,4	1,3	3,5	6,2

The characteristic resistance for pull-out failure, concrete cone failure, concrete pry-out failure and concrete edge failure can be designed according to TR020 / CEN/TS 1992-4.

### Wedge Anchor BZ-IG

#### Performance

Characteristic values for **tension** and **shear loads** under fire exposure, BZ-IG  
 cracked and non-cracked concrete C20/25 to C50/60,  
 design acc. to TR 020 or CEN/TS 1992-4, Annex D

**Annex C13**

**Table C14: Displacements under tension load, BZ-IG**

Anchor size			M6	M8	M10	M12
Tension load in cracked concrete	N	[kN]	2,0	3,6	4,8	8,0
Displacements	$\delta_{N0}$	[mm]	0,6	0,6	0,8	1,0
	$\delta_{N\infty}$	[mm]	0,8	0,8	1,2	1,4
Tension load in non-cracked concrete	N	[kN]	4,8	6,4	8,0	12,0
Displacements	$\delta_{N0}$	[mm]	0,4	0,5	0,7	0,8
	$\delta_{N\infty}$	[mm]	0,8	0,8	1,2	1,4

**Table C15: Displacements under shear load, BZ-IG**

Anchor size			M6	M8	M10	M12
Shear load in cracked and non-cracked concrete	V	[kN]	4,2	5,3	6,2	16,9
Displacements	$\delta_{v0}$	[mm]	2,8	2,9	2,5	3,6
	$\delta_{v\infty}$	[mm]	4,2	4,4	3,8	5,3

**Wedge Anchor BZ-IG****Performance**

Displacements under tension load and under shear load

**Annex C14**