

DECLARATION OF PERFORMANCE
DoP No. MKT-410 - en

1. Unique identification code of the product-type: **MKT Injection System VMU**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-05/0253, Annex 1 and 2
Batch number: see packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

generic type	bonded anchor
for use in	non-cracked concrete C20/25 – C50/60 (EN 206)
option	7
loading	static or quasi-static
material	<u>hot-dip galvanized steel:</u> dry internal conditions only covered sizes: M8, M10, M12, M16, M20, M24, M30 <u>zinc-plated steel:</u> dry internal conditions only covered sizes: M8, M10, M12, M16, M20, M24, M30 <u>stainless steel (marking A4):</u> internal and external use without particular aggressive conditions covered sizes: M8, M10, M12, M16, M20, M24, M30 <u>high corrosion resistant steel (marking HCR):</u> internal and external use with particular aggressive conditions covered sizes: M8, M10, M12, M16, M20, M24, M30
temperature range (if applicable)	Range I: -40 °C to +80 °C Range II: -40 °C to +120 °C

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

MKT Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
D - 67685 Weilerbach

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 1**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

issued **Deutsches Institut für Bautechnik, Berlin**
ETA-05/0253
on the basis of **ETAG 001-5**

The notified body 0756-CPD performed under system 1

- (i) determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
- (ii) initial inspection of the manufacturing plant and of factory production control;
- (iii) continuous surveillance, assessment and evaluation of factory production control.

and issued: Certificate of conformity 0756-CPD-0120

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
characteristic resistance for tension	ETAG 001, Annex C	ETA-05/0253, Annex 7	ETAG 001
characteristic resistance for shear	ETAG 001, Annex C	ETA-05/0253, Annex 8	
minimum spacing and minimum edge distance	ETAG 001, Annex C	ETA-05/0253, Annex 5	
displacement for serviceability limit state	ETAG 001, Annex C	ETA-05/0253, Annex 7, 8	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:


Lore Weustenhagen
 (General Manager)
 Weilerbach, 30.06.2013

i.V. 
Dipl.-Ing. Detlef Bigalke
 (Head of product development)



Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 5

MKT injection adhesive VMU

SDS no. : 288352

V001.0

Revision: 30.01.2009

printing date: 10.02.2009

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

MKT injection adhesive VMU, Comp. A

Intended use:

MKT injection system VMU

Company name:

MKT Metall-Kunststoff-Technik GmbH & Co. KG

Auf dem Immel 2

D-67685 Weilerbach

Phone: +49 (0) 6374/9116-0

Fax-no.: +49 (0) 6374/9116-60

E-Mail: Responsible for the safety data sheet: mkt@mkt-duebel.de

Emergency information:

Advisory office in case of poisoning: +49 (0) 89/19240 (Munich)

2. Hazards identification

The product is classified as hazardous within the meaning of the valid (EU) preparation directive.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Persons suffering from allergic reactions to acrylates should avoid contact with the product.

3. Composition / information on ingredients

General chemical description:

Resin

Base substances of preparation:

Inorganic fillers

Methacrylates

Declaration of ingredients according to (EC) No 1907/2006:

Hazardous components CAS-No.	EINECS	content	Classification
1,6-Hexanediyl bismethacrylate 6606-59-3	229-551-7	< 10 %	Xi - Irritant; R36/37/38 N - Dangerous for the environment; R51/53
N,N-Diethylaniline 91-66-7	202-088-8	< 0,5 %	T - Toxic; R23/24/25 R33 N - Dangerous for the environment; R51, R53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

4. First aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

Special protection equipment for firefighters:

Wear self-contained breathing apparatus.
Wear protective equipment.

Hazardous combustion products:

Carbon dioxide., carbon monoxide

Additional information:

Dispose of combustion residues and contaminated fire-fighting water in accordance with statutory regulations.

6. Accidental release measures

Personal precautions:

Avoid contact with eyes.
Keep away from sources of ignition.
Ensure adequate ventilation.
Danger of slipping on spilled product.

Environmental precautions:

Do not empty into drains / surface water / ground water.

Clean-up methods:

Remove mechanically.
Dispose of contaminated material as waste according to item 13.

7. Handling and storage

Handling:

Avoid skin and eye contact.
Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.

Storage:

Store in sealed original container protected against moisture.
Store in a cool, dry place.
Storage at 5 to 25°C is recommended.
Keep container in a well ventilated place.
Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

8. Exposure controls / personal protection

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Hand protection:

For shorttime contact (e.g. as protection against splashes) protective gloves made from butyl rubber are recommended according to EN 374.

material thickness > 0.7 mm

Perforation time > 60 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Skin protection:

suitable protective clothing

General protection and hygiene measures:

Wash off any dirt that gets onto the skin with lots of soap and water, skin care.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

9. Physical and chemical properties

General characteristics:

Appearance

Paste
pasty
light beige
Characteristic

Odor:

Characteristic

Phys./chem. properties:

Density

1,55 g/cm³

(23 °C (73.4 °F))

Solubility (qualitative)

practically insoluble

(20 °C (68 °F); Solvent: Water)

10. Stability and reactivity

Conditions to avoid:

No decomposition if used according to specifications.

Materials to avoid:

Reaction with oxidants.

Reaction with strong acids.

Hazardous decomposition products:

None known

11. Toxicological information

General toxicological information:

To the best of our knowledge no harmful effects are to be expected if the product is handled and used properly.
Persons suffering from allergic reactions to acrylates should avoid contact with the product.

12. Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

13. Disposal considerations

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

After curing with component B :

Can be added to household waste in small quantities.

The valid EEC waste code numbers are not product-related but are largely source-related. The manufacturer is therefore unable to specify EEC waste codes for the articles or products used in the various sectors. These can be requested from the manufacturer.

Disposal of uncleaned packages:

Only well-emptied containers with dried or cured product residues and without solvent vapors can be recycled.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. Regulations - classification and identification

Risk phrases:

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicated by codes in this safety data sheet are as follows:

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R33 Danger of cumulative effects.

R36/37/38 Irritating to eyes, respiratory system and skin.

R51 Toxic to aquatic organisms.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 6

MKT injection adhesive VMU

SDS no. : 288352

V001.0

Revision: 30.01.2009

printing date: 10.02.2009

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

MKT injection adhesive VMU, Comp. B

Intended use:

MKT injection system VMU

Company name:

MKT Metall-Kunststoff-Technik GmbH & Co. KG

Auf dem Immel 2

D-67685 Weilerbach

Phone: +49 (0) 6374/9116-0

Fax-no.: +49 (0) 6374/9116-60

E-Mail: Responsible for the safety data sheet: mkt@mkt-duebel.de

Emergency information:

Advisory office in case of poisoning: +49 (0) 89/19240 (Munich)

2. Hazards identification

The product is classified as hazardous within the meaning of the valid (EU) preparation directive.

Xi - Irritant

R43 May cause sensitization by skin contact.

Persons suffering from allergic reactions to peroxides should avoid contact with the product.

3. Composition / information on ingredients

General chemical description:

hardener component

Base substances of preparation:

Dibenzoyl peroxide

Inorganic fillers

Declaration of ingredients according to (EC) No 1907/2006:

Hazardous components CAS-No.	EINECS	content	Classification
Dibenzoyl peroxide 94-36-0	202-327-6	>= 10 - < 20 %	E - Explosive; R3 O - Oxidizing; R7 Xi - Irritant; R36, R43
Glycerol 56-81-5	200-289-5	>= 1 - <= 10 %	
2-Ethylhexyl benzoate 5444-75-7	226-641-8	>= 1 - < 10 %	R53
Oxydipropyl dibenzoate 27138-31-4	248-258-5	>= 1 - < 2,5 %	N - Dangerous for the environment; R51/53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

4. First aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

carbon dioxide
Powder
fine water spray
water spray jet

Extinguishing media which must not be used for safety reasons:

Foam.
High pressure waterjet

Special protection equipment for firefighters:

Wear self-contained breathing apparatus.
Wear protective equipment.

Hazardous combustion products:

Carbon dioxide., carbon monoxide

Additional information:

Dispose of combustion residues and contaminated fire-fighting water in accordance with statutory regulations.

6. Accidental release measures

Personal precautions:

Avoid contact with skin and eyes.
Keep away from sources of ignition.
Ensure adequate ventilation.

Environmental precautions:

Do not empty into drains / surface water / ground water.

Clean-up methods:

Remove mechanically.
Dispose of contaminated material as waste according to item 13.

7. Handling and storage

Handling:

Avoid skin and eye contact.
Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.
Throw out sparks on burning.

Storage:

- Store in sealed original container protected against moisture.
- Store in a cool place in closed original container.
- Store in a cool, dry place.
- Storage at 5 to 25°C is recommended.
- store in dark
- Do not store together with food or other consumables (coffee, tea, tobacco, etc.).
- Do not store together with highly flammable substances (F or F+).

8. Exposure controls / personal protection

Components with specific control parameters for workplace:

- Valid for
 - Great Britain
- Basis
 - UK EH40 WELs

Ingredient	ppm	mg/m ³	Type	Category	Remarks
DIBENZOYL PEROXIDE 94-36-0		5	Time Weighted Average (TWA).		EH40 WEL
GLYCEROL, MIST 56-81-5		10	Time Weighted Average (TWA).		EH40 WEL

Engineering controls:

No further information, see section 7.

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Hand protection:

For shorttime contact (e.g. as protection against splashes) protective gloves made from butyl rubber are recommended according to EN 374.
 material thickness > 0.7 mm
 Perforation time > 60 minutes
 In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Skin protection:

suitable protective clothing

General protection and hygiene measures:

- Wash off any dirt that gets onto the skin with lots of soap and water, skin care.
- Do not eat, drink or smoke while working.
- Wash hands before work breaks and after finishing work.

9. Physical and chemical properties

General characteristics:

Appearance	Paste solid Black
Odor:	Characteristic

Phys./chem. properties:

Density (20 °C (68 °F))	0,97 - 1,03 g/cm ³
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Insoluble

10. Stability and reactivity

Conditions to avoid:

Temperatures over appr. 80 °C

Materials to avoid:

Reaction with oxidants.

Hazardous decomposition products:

None known

11. Toxicological information

General toxicological information:

Persons suffering from allergic reactions to peroxides should avoid contact with the product.

Eye irritation:

Primary eye irritation: slightly irritating, does not require labeling

Sensitizing:

May cause sensitization by skin contact.

12. Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

13. Disposal considerations

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

After curing with component A :

Can be added to household waste in small quantities.

The valid EEC waste code numbers are not product-related but are largely source-related. The manufacturer is therefore unable to specify EEC waste codes for the articles or products used in the various sectors. These can be requested from the manufacturer.

Disposal of uncleaned packages:

Only well-emptied containers with dried or cured product residues and without solvent vapors can be recycled.

14. Transport information

Road transport ADR:

Class: 5.2
Packaging group:
Classification code: P1
Hazard ident. number:
UN no.: 3108
Label: 5.2
Technical name: ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

Railroad transport RID:

Class: 5.2
Packaging group:
Classification code: P1
Hazard ident. number: 539
UN no.: 3108
Label: 5.2
Technical name: ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

Inland water transport ADN:

Class: 5.2
Packaging group:
Classification code: P1
Hazard ident. number:
UN no.: 3108
Label: 5.2
Technical name: ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

Marine transport IMDG:

Class: 5.2
Packaging group:
UN no.: 3108
Label: 5.2
EmS: F-J ,S-R
Seawater pollutant:
Proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

Air transport IATA:

Class: 5.2
Packaging group:
Packaging instructions (passenger) 510
Packaging instructions (cargo) 513
UN no.: 3108
Label: 5.2
Proper shipping name: Organic peroxide type E, solid (Dibenzoyl peroxide)

15. Regulations - classification and identification

Indication of danger:

Xi - Irritant



Contains

Dibenzoyl peroxide

Risk phrases:

R43 May cause sensitization by skin contact.

Safety phrases:

S2 Keep out of the reach of children.

S3/7 Keep container tightly closed in a cool place.

S14 Keep away from dirt, rust, alkalis, acids and accelerators.

S24/25 Avoid contact with skin and eyes.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicated by codes in this safety data sheet are as follows:

R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.

R36 Irritating to eyes.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

R7 May cause fire.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

MKT injection adhesive VMU express

V001.0
Revision: 19.07.2011
printing date: 13.09.2011

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier:

MKT injection adhesive VMU express, Comp A

Relevant identified uses of the substance or mixture and uses advised against:

Intended use:
compound mortar

Company name:

MKT Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
D-67685 Weilerbach
Phone: +49 (0) 6374/9116-0
E-Mail: Responsible for the safety data sheet: mkt@mkt-duebel.de

SECTION 2: Hazards identification

Classification of the substance or mixture:**Classification (DPD):**

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Label elements (DPD):**Risk phrases:**

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S2 Keep out of the reach of children.
S46 If swallowed, seek medical advice immediately and show this container or label.
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Other hazards:

Persons suffering from allergic reactions to acrylates should avoid contact with the product.

SECTION 3: Composition/information on ingredients

General chemical description:

Resin

Base substances of preparation:

Inorganic fillers
Methacrylates

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EINECS REACH-Reg No.	content	Classification
Hexanediol dimethacrylate 6606-59-3	229-551-7	< 10 %	Specific target organ toxicity - single exposure 3 H335 Serious eye irritation 2 H319 Skin irritation 2 H315
N,N-Diethylaniline 91-66-7	202-088-8	< 0,5 %	Acute toxicity 3; Oral H301 Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 2 H411

**Only dangerous ingredients for which a CLP classification is already available are displayed in this table.
For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EINECS REACH-Reg No.	content	Classification
Hexanediol dimethacrylate 6606-59-3	229-551-7	< 10 %	Xi - Irritant; R36/37/38 N - Dangerous for the environment; R51/53
N,N-Diethylaniline 91-66-7	202-088-8	< 0,5 %	T - Toxic; R23/24/25 N - Dangerous for the environment; R51, R53 R33
4-tert-Butylpyrocatechol 98-29-3	202-653-9	< 1 %	C - Corrosive; R34 Xn - Harmful; R21/22 N - Dangerous for the environment; R51/53

**For full text of the R-Phrases indicated by codes see section 16 'Other Information'.
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures**Description of first aid measures:**

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

Most important symptoms and effects, both acute and delayed:

No data available.

V001.0

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

SECTION 5: Firefighting measures**Extinguishing media:****Suitable extinguishing media:**

carbon dioxide
powder
Fine water spray
water spray jet

Extinguishing media which must not be used for safety reasons:

High pressure waterjet
foam

Special hazards arising from the substance or mixture:In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.**Advice for firefighters:**

Wear self-contained breathing apparatus.
Wear protective equipment.

SECTION 6: Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Avoid contact with eyes.
Ensure adequate ventilation.
Wear protective equipment.
Danger of slipping on spilled product.

Environmental precautions:

Do not empty into drains / surface water / ground water.

Methods and material for containment and cleaning up:

Remove mechanically.
Dispose of contaminated material as waste according to Chapter 13.

Reference to other sections:

See advice in chapter 8

SECTION 7: Handling and storage**Precautions for safe handling:**

Avoid skin and eye contact.
Ensure that workrooms are adequately ventilated.

Hygiene measures:

Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.

Conditions for safe storage, including any incompatibilities:

Store in sealed original container protected against moisture.
Store in a cool, dry place.
Storage at 5 to 25°C is recommended.
Keep container in a well ventilated place.
Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

V001.0

Specific end use(s):
compound mortar

SECTION 8: Exposure controls/personal protection

Control parameters:

Valid for
Great Britain

None

Exposure controls:

Respiratory protection:

When processing large amounts.
Suitable breathing mask when there is inadequate ventilation.
Filter: A - P2

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

Skin protection:

Suitable protective clothing

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties:

Appearance	paste pasty light beige
Odor	characteristic
pH	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density (23 °C (73.4 °F))	1,55 g/cm ³
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	practically insoluble
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

V001.0

Other information:

No data available / Not applicable

SECTION 10: Stability and reactivity**Reactivity:**

Reaction with oxidants.
Reaction with strong acids.

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

See section reactivity

Conditions to avoid:

None if used for intended purpose.

Incompatible materials:

None if used properly.

Hazardous decomposition products:

None known

SECTION 11: Toxicological information**General toxicological information:**

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.
Persons suffering from allergic reactions to acrylates should avoid contact with the product.

SECTION 12: Ecological information**General ecological information:**

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.
Do not empty into drains, soil or bodies of water.

V001.0

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
N,N-Diethylaniline 91-66-7	LC50	16,4 mg/l	Fish	96 h	Pimephales promelas	EPA OPP 72-1 (Fish Acute Toxicity Test)
N,N-Diethylaniline 91-66-7	EC50	1 - 1,6 mg/l	Daphnia	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
N,N-Diethylaniline 91-66-7	EC50	5,6 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	
4-tert-Butylpyrocatechol 98-29-3	EC50	1,4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
N,N-Diethylaniline 91-66-7		aerobic	> 90 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
N,N-Diethylaniline 91-66-7	3,17	17 - 125	56 d	Cyprinus carpio	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
N,N-Diethylaniline 91-66-7						
4-tert-Butylpyrocatechol 98-29-3	2,94					

SECTION 13: Disposal considerations**Waste treatment methods:**

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information**Road transport ADR:**

Not dangerous goods

Railroad transport RID:

Not dangerous goods

V001.0

Inland water transport ADN:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

SECTION 15: Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture:**

VOC content 0,00 %
(VOCV 814.018 VOC regulation
CH)

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

R21/22 Harmful in contact with skin and if swallowed.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R33 Danger of cumulative effects.
R34 Causes burns.
R36/37/38 Irritating to eyes, respiratory system and skin.
R51 Toxic to aquatic organisms.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53 May cause long-term adverse effects in the aquatic environment.

H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

MKT injection adhesive VMU express

V001.0
Revision: 19.07.2011
printing date: 13.09.2011

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier:

MKT injection adhesive VMU express, Comp. B

Relevant identified uses of the substance or mixture and uses advised against:

Intended use:
compound mortar

Company name:

MKT Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
D-67685 Weilerbach
Phone: +49 (0) 6374/9116-0
E-Mail: Responsible for the safety data sheet: mkt@mkt-duebel.de

SECTION 2: Hazards identification

Classification of the substance or mixture:

Classification (DPD):

Sensitizing
R43 May cause sensitisation by skin contact.

Label elements (DPD):

Xi - Irritant



Risk phrases:

R43 May cause sensitisation by skin contact.

Safety phrases:

S2 Keep out of the reach of children.
S3/7 Keep container tightly closed in a cool place.
S14 Keep away from dirt, rust, alkalis, acids and accelerators.
S24/25 Avoid contact with skin and eyes.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S46 If swallowed, seek medical advice immediately and show this container or label.

Contains:

Dibenzoyl peroxide

Other hazards:

Persons suffering from allergic reactions to peroxides should avoid contact with the product.

V001.0

SECTION 3: Composition/information on ingredients

General chemical description:

Hardener

Base substances of preparation:

Dibenzoyl peroxide

Inorganic fillers

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EINECS REACH-Reg No.	content	Classification
Dibenzoyl peroxide 94-36-0	202-327-6	>= 10- < 20 %	Organic peroxides B H241 Serious eye irritation 2 H319 Skin sensitizer 1 H317

Only dangerous ingredients for which a CLP classification is already available are displayed in this table.

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EINECS REACH-Reg No.	content	Classification
Dibenzoyl peroxide 94-36-0	202-327-6	>= 10 - < 20 %	E - Explosive; R3 Xi - Irritant; R36 O - Oxidizing; R7 R43

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

Description of first aid measures:
General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse the mouth. Drink 1-2 glasses of water.

Most important symptoms and effects, both acute and delayed:

SKIN: Rash, Urticaria.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

SECTION 5: Firefighting measures**Extinguishing media:****Suitable extinguishing media:**

- powder
- Carbon dioxide.
- water spray jet
- Fine water spray

Extinguishing media which must not be used for safety reasons:

- foam
- High pressure waterjet

Special hazards arising from the substance or mixture:

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

Advice for firefighters:

- Wear self-contained breathing apparatus.
- Wear protective equipment.

Additional information:

Dispose of combustion residues and contaminated fire-fighting water in accordance with statutory regulations.

SECTION 6: Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

- Avoid contact with skin and eyes.
- Ensure adequate ventilation.
- Wear protective equipment.
- Danger of slipping on spilled product.

Environmental precautions:

Do not empty into drains / surface water / ground water.

Methods and material for containment and cleaning up:

- Remove mechanically.
- Dispose of contaminated material as waste according to Chapter 13.

Reference to other sections:

See advice in chapter 8

SECTION 7: Handling and storage**Precautions for safe handling:**

- Avoid skin and eye contact.
- Throw out sparks on burning.

Hygiene measures:

- Do not eat, drink or smoke while working.
- Wash hands before work breaks and after finishing work.

Conditions for safe storage, including any incompatibilities:

- Store in sealed original container protected against moisture.
- Store in a cool place in closed original container.
- Store in a cool, dry place.
- Storage at 5 to 25°C is recommended.
- store in dark
- Do not store together with food or other consumables (coffee, tea, tobacco, etc.).
- Do not store together with highly flammable substances (F or F+).

V001.0

Specific end use(s):
compound mortar

SECTION 8: Exposure controls/personal protection

Control parameters:
Valid for
Great Britain

Ingredient	ppm	mg/m ³	Type	Category	Remarks
GLYCEROL, MIST 56-81-5		10	Time Weighted Average (TWA):		EH40 WEL

Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.
Filter: A - P2

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

Skin protection:

Suitable protective clothing

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties:

Appearance	paste paste black
Odor	characteristic
pH	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	116 °C (240.8 °F); no method
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density	No data available / Not applicable
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Insoluble
(20 °C (68 °F); Solvent: Water)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

V001.0

Other information:

No data available / Not applicable

SECTION 10: Stability and reactivity**Reactivity:**

Reaction with oxidants.

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

See section reactivity

Conditions to avoid:

Temperatures over appr. 80 °C

Incompatible materials:

None if used properly.

Hazardous decomposition products:

None known

SECTION 11: Toxicological information**General toxicological information:**

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. Persons suffering from allergic reactions to peroxides should avoid contact with the product.

Eye irritation:

Primary eye irritation: slightly irritating, does not require labeling

Sensitizing:

May cause sensitization by skin contact.

SECTION 12: Ecological information**General ecological information:**

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. Do not empty into drains, soil or bodies of water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	LC50	2 mg/l	Fish	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
Dibenzoyl peroxide 94-36-0	EC50	2,91 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

V001.0

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Dibenzoyl peroxide 94-36-0	readily biodegradable		> 60 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Dibenzoyl peroxide 94-36-0	3,46					

SECTION 13: Disposal considerations
--

Waste treatment methods:

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 09 Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information
--

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content 0,0 %
 (VOCV 814.018 VOC regulation
 CH)

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.

R36 Irritating to eyes.

R43 May cause sensitisation by skin contact.

R7 May cause fire.

H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.