

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

VME, Comp. A

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name:	MKT Metall-Kunststoff-Technik GmbH & Co. KG	
Street:	Auf dem Immel 2	
Place:	67685 Weilerbach	
Telephone:	+49(0)6374-91 16-0	Telefax: +49(0)6374-91 16-60
e-mail:	info@mkt.de	
Internet:	www.mkt.de	

1.4. Emergency telephone number:

+49 (0) 89-19240 (24h)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.


Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**epoxy resin (number average molecular weight \leq 700), reaction product: bisphenol-A-(epichlorhydrin)Reaction product: bisphenol-F-(epichlorhydrin) Epoxy resin (number average molecular weight \leq 700)

1,6-Bis(2,3-epoxypropoxy)hexane

Signal word: Warning**Pictograms:****Hazard statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 2 of 12

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container to in accordance with local/regional/national/international regulation.

Special labelling of certain mixtures

EUH205	Contains epoxy constituents. May produce an allergic reaction.
--------	--

2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	25-50 %
	500-033-5	603-074-00-8
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H319 H315 H317 H411	
9003-36-5	Reaction product: bisphenol-F-(epichlorhydrin) Epoxy resin (number average molecular weight =< 700)	10-20 %
	500-006-8	01-2119454392-40
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane	10-20 %
	240-260-4	01-2119463471-41
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412	
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)	1-10 %
	Eye Irrit. 2; H319	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 3 of 12

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam.
Extinguishing powder
Water spray jet
Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet
Foam.

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.
When using do not eat, drink or smoke.
Wash hands before breaks and after work.

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 4 of 12

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Keep only in the original container in a cool, well-ventilated place.

Advice on storage compatibility

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature : 5-35°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)			
Worker DNEL, long-term		dermal	systemic	8,33 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	12,25 mg/m ³
Worker DNEL, acute		inhalation	systemic	12,25 mg/m ³
Worker DNEL, acute		dermal	systemic	8,33 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	3,571 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	3,571 mg/kg bw/day
9003-36-5	Reaction product: bisphenol-F-(epichlorhydrin) Epoxy resin (number average molecular weight =< 700)			
Worker DNEL, acute		dermal	local	8,3 mg/cm ²
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m ³
Consumer DNEL, long-term		dermal	systemic	62,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m ³
Consumer DNEL, long-term		oral	systemic	6,25 mg/kg bw/day
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane			
Worker DNEL, long-term		dermal	systemic	2,8 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2,9 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 5 of 12

PNEC values

CAS No	Substance	Value
Environmental compartment		
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	
Freshwater		0,006 mg/l
Marine water		0,006 mg/l
Freshwater sediment		0,996 mg/l
Marine sediment		0,996 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
9003-36-5	Reaction product: bisphenol-F-(epichlorhydrin) Epoxy resin (number average molecular weight =< 700)	
Freshwater		0,003 mg/l
Marine water		0,0003 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,0294 mg/kg
Secondary poisoning		0,0254 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,237 mg/kg
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane	
Freshwater		0,0115 mg/l

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): 0,7mm NBR (Nitrile rubber) >480min (EN374)

Wearing time with permanent contact 0,7mm NBR (Nitrile rubber) >480min (EN374)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 6 of 12

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Paste
Colour: light beige
pH-Value: not determined

Changes in the physical state

Melting point: not determined
Initial boiling point and boiling range: not determined
Flash point: not applicable

Flammability

Solid: not determined
Gas: not applicable

Lower explosion limits: not determined
Upper explosion limits: not determined

Auto-ignition temperature

Solid: not determined
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,49 g/cm³

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent
Violent reaction with: Alkali (Iye), Etchant and acids

10.4. Conditions to avoid

none

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 7 of 12

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)				
	oral	LD50 mg/kg	11400	Rat	
9003-36-5	Reaction product: bisphenol-F-(epichlorhydrin) Epoxy resin (number average molecular weight =< 700)				
	oral	LD50 mg/kg	>2000	Rat	
	dermal	LD50 mg/kg	>2000	Rat	
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane				
	oral	LD50 mg/kg	2900	Rat	
	dermal	LD50 mg/kg	> 2000	Rat	
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)				
	oral	LD50 mg/kg	20700	Mouse	
	dermal	LD50 mg/kg	2000	Rabbit	

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Further information

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)					
	Acute fish toxicity	LC50	1,3 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute crustacea toxicity	EC50	2,1 mg/l	48 h	Daphnia magna (Big water flea)	
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna (Big water flea)	
9003-36-5	Reaction product: bisphenol-F-(epichlorhydrin) Epoxy resin (number average molecular weight =< 700)					
	Acute fish toxicity	LC50	2,54 mg/l	96 h	Carassius auratus (goldfish)	
	Acute crustacea toxicity	EC50	2,55 mg/l	48 h	Daphnia pulex (water flea)	
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane					
	Acute fish toxicity	LC50	30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	2,64-3,78

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 9 of 12

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol A/F Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Classification code: M7
Special Provisions: 274 335 375 601
Limited quantity: 5 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: E

Other applicable information (land transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADR/RID

Inland waterways transport (ADN)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol A/F Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Classification code: M7
Special Provisions: 274 335 375 601
Limited quantity: 5 kg
Excepted quantity: E1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 10 of 12

Other applicable information (inland waterways transport)

No dangerous goods in packaging until 5kg according special instruction 375 ADN

Marine transport (IMDG)

14.1. UN number:	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol A/F Epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9



Special Provisions:	274, 335, 966, 967, 969
Limited quantity:	5 kg
Excepted quantity:	E1
EmS:	F-A, S-F

Other applicable information (marine transport)

No dangerous goods in packaging until 5kg according 2.10.2.7 IMDG-Code

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol A/F Epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9



Special Provisions:	A97 A158 A179 A197
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y956
Excepted quantity:	E1
IATA-packing instructions - Passenger:	956
IATA-max. quantity - Passenger:	400 kg
IATA-packing instructions - Cargo:	956
IATA-max. quantity - Cargo:	400 kg

Other applicable information (air transport)

No dangerous goods in packaging until 5kg according A197 IATA-DGA

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

**14.6. Special precautions for user**

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 11 of 12

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

VOC content: 0,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 8,10.

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Dangerous Goods Code

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 2: Long-term aquatic hazard, Category 2

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitization, Category 1

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 09.04.2018

Product code: SDB0007

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 2 of 13

Pictograms:



Hazard statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P405	Store locked up.
P501	Dispose of contents/container to in accordance with local/regional/national/international regulation.

2.3. Other hazards

This substance meets the PBT criteria of REACH, Annex XIII.
Contains Amines. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 3 of 13

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			30 - < 35 %
	220-666-8			
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H318 H317 H412			
77138-45-5	Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine			20 - < 25 %
	500-263-6			
	Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1; H314 H318 H317			
57214-10-5	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)			20 - < 25 %
	500-137-0		01-2119966906-20	
	Skin Corr. 1C, Skin Sens. 1B, Aquatic Chronic 3; H314 H317 H412			
1477-55-0	m-Phenylenebis(methylamine)			15 - < 20 %
	216-032-5		01-2119480150-50	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1B, Aquatic Chronic 3; H332 H302 H314 H317 H412			
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol			5 - < 10 %
	202-013-9		01-2119560597-27	
	Skin Corr. 1B, Skin Sens. 1B, Aquatic Chronic 3; H314 H317 H412			
100-51-6	benzyl alcohol			5 - < 10 %
	202-859-9		01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			
111-40-0	diethylenetriamine			5 - < 10 %
	203-865-4		01-2119473793-27	
	Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, STOT SE 3; H330 H312 H302 H314 H317 H335			
108-95-2	phenol			1 - < 5 %
	203-632-7		01-2119471329-32	
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, STOT RE 2, Aquatic Chronic 2; H341 H331 H311 H301 H314 H318 H373 H411			
80-05-7	Bisphenol A			1 - < 5 %
	201-245-8		01-2119457856-2	
	Repr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H360F H318 H317 H335			
71074-89-0	Bis[(dimethylamino)methyl]phenol			1 - < 5 %
	275-162-0			
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1; H302 H314 H318			

Full text of H and EUH statements: see section 16.

Further Information

REACH Art. 59, SVHC list (Candidate list of Substances of Very High Concern for authorisation): Bisphenol A

SECTION 4: First aid measures

4.1. Description of first aid measures

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 4 of 13

General information

Change contaminated, saturated clothing.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing powder

Water spray jet

Unsuitable extinguishing media

Full water jet

Foam.

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.

Use personal protection equipment.

Special danger of slipping by leaking/spilling product.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Take up mechanically.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 5 of 13

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

When using do not eat, drink or smoke.

Use protective skin cream before handling the product.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Keep/Store only in original container.

Advice on storage compatibility

Do not use for products which come into contact with the food stuffs.

Store in a well-ventilated place. Keep cool.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature 5-35°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-40-0	2,2'-Iminodi(ethylamine)	1	4.3		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
80-05-7	Bisphenol A, inhalable dust	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL

8.2. Exposure controls



Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: Wear eye/face protection.

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 6 of 13

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): 0,7mm NBR (Nitrile rubber) >480min (EN374)

Wearing time with permanent contact 0,7mm NBR (Nitrile rubber) >480min (EN374)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Paste	
Colour:	black / red	
Odour:	characteristic	
pH-Value:		not applicable

Changes in the physical state

Melting point:		not determined
Initial boiling point and boiling range:		not determined
Flash point:		not applicable

Flammability

Solid:		not determined
Gas:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined

Auto-ignition temperature

Solid:		not determined
Gas:		not applicable
Decomposition temperature:		not determined

Oxidizing properties

Not oxidising.		
Vapour pressure:		not determined
Density (at 20 °C):		1,07 g/cm ³
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	

Solubility in other solvents

not determined		
Partition coefficient:		not determined
Vapour density:		not determined
Evaporation rate:		not determined

9.2. Other information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 7 of 13

Solid content:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 8 of 13

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	LD50 1030 mg/kg	Rat		
	dermal	ATE 1100 mg/kg			
1477-55-0	m-Phenylenebis(methylamine)				
	oral	LD50 930 mg/kg	Rat		
	dermal	LD50 2000 mg/kg	Rabbit		
	inhalative (1 h) vapour	LC50 3,89 mg/l	Rat		
	inhalative aerosol	ATE 1,5 mg/l			
100-51-6	benzyl alcohol				
	oral	LD50 1230 mg/kg	Rat	GESTIS	
	inhalative vapour	ATE 11 mg/l			
	inhalative aerosol	ATE 1,5 mg/l			
111-40-0	diethylenetriamine				
	oral	LD50 1540 mg/kg	Rat		
	dermal	LD50 672 mg/kg	Rabbit		
	inhalative vapour	ATE 0,5 mg/l			
	inhalative aerosol	ATE 0,05 mg/l			
108-95-2	phenol				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
	inhalative vapour	ATE 3 mg/l			
	inhalative aerosol	ATE 0,5 mg/l			
80-05-7	Bisphenol A				
	oral	LD50 3250 mg/kg	Rat		
	dermal	LD50 3000 mg/kg	Rabbit		
71074-89-0	Bis[(dimethylamino)methyl]phenol				
	oral	ATE 500 mg/kg			

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Further information

This mixture is placed on the market in a form, in which there can be no aerosol formation when used as intended. It may only be used for applications where aerosol formation is excluded. In accordance with Article 6 of the CLP Regulation 1272/2008/EU, therefore, the classification and labeling for inhalation toxicity is not required.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 9 of 13

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
111-40-0	diethylenetriamine					
	Acute fish toxicity	LC50	430 mg/l	96 h	Leuciscus idus	
	Acute algae toxicity	ErC50 mg/l	1164	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 mg/l	53,5	48 h	Daphnia magna	
108-95-2	phenol					
	Acute algae toxicity	ErC50	229 mg/l	72 h		GESTIS
80-05-7	Bisphenol A					
	Acute fish toxicity	LC50	4,6 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	2,73	96 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50	3,9 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	1,9
100-51-6	benzyl alcohol	1,05
111-40-0	diethylenetriamine	-2,13
108-95-2	phenol	1,5
80-05-7	Bisphenol A	3,32

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 10 of 13

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8



Classification code:	C8
Special Provisions:	274
Limited quantity:	1 kg
Excepted quantity:	E2
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number:	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8



Classification code:	C8
Special Provisions:	274

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 11 of 13

Limited quantity: 1 kg
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Special Provisions: 223, 274
 Limited quantity: 1 kg
 Excepted quantity: E2
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Special Provisions: A3 A803
 Limited quantity Passenger: 5 kg
 Passenger LQ: Y844
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 859
 IATA-max. quantity - Passenger: 15 kg
 IATA-packing instructions - Cargo: 863
 IATA-max. quantity - Cargo: 50 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
 Bisphenol A

Restrictions on use (REACH, annex XVII):

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 12 of 13

Entry 3: 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 2,4,6-tris(dimethylaminomethyl)phenol; benzyl alcohol; diethylenetriamine

Entry 66: Bisphenol A

Additional information

VOC content: 28,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 14.

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ATE: Acute Toxicity Estimates

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 2: Long-term aquatic hazard, Category 2

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Acute Tox. 2: Acute toxicity, Category 2

Acute Tox. 3: Acute toxicity, Category 3

Acute Tox. 4: Acute toxicity, Category 4

Eye Dam. 1: Serious eye damage/eye irritation, Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Muta. 2: Germ cell mutagenicity, Category 2

Repr. 1B: Reproductive toxicity, Category 1B

Skin Corr. 1B: Skin corrosion/irritation, Category 1B

Skin Corr. 1C: Skin corrosion/irritation, Category 1C

STOT RE 2: Specific target organ toxicity (repeated exposure), Category 2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 09.04.2018

Product code: SDB0008

Page 13 of 13

STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Repr. 1B; H360F	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)