Manufacturer MKT GmbH & Co.KG

Product Name MKT Injection Mortar VME

# **Product Rating**

• The product fulfills the requirements for adhesives and sealants and contribute to achieve one LEED credit within IEQ Credit 4.1.

Indoor Environmental Qual	ity (IEQ) - LEED Category		
IEQ Credit 4.1: Low Emitting	Materials: Adhesives and Sealants	1 Point	<b>✓</b>
IEQ Credit 4.2: Low Emitting	Materials: Paints and Coatings	1 Point	0
IEQ Credit 4.3: Low Emitting	Materials: Flooring Systems	1 Point	0
IEQ Credit 4.4: Low Emitting	Materials: Composite Wood and Agrifiber Products	1 Point	0
Materials and Resources (N	/IR) - LEED Category		
MR Credit 4: Recycled Co	ontent	1-2 Points	_
MR Credit 5: Regional Ma	nterials	1-2 Points	See Location
MR Credit 6: Rapidly Rend	ewable Materials	1 Point	0
MR Credit 7: Certified Wo	ood	1 Point	0

### **Product Characteristics**

Two component epoxy mortar, approved for post installed rebar connections as well as for fixings into concrete and by using threaded anchor rods or rebars. Due to long curing time especially suitable for warm environments as well as for deep drill holes.

# About LEED & Products - www.usgbc.org

This declaration helps to assess products easily according the certification system LEED® 2009 New Construction and Major Renovations NC & CS (excluded SCHOOLS). Products are not reviewed or certified by LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information about LEED visit www.usgbc.org/leed. The project team or the manufacturer is responsible to declare the compliance with the project requirements to achieve LEED points.

Below you find an explanation of the symbols. Detailed information are on the next pages.

- Credit requirements fulfilled the credit point can be achieved
- Credit is not applicable to this product
- 22% X% of the product comply with the credit requirement
- Required data not specified for required data contact manufacturer
- Credit requirements are not fulfilled

Manufacturer MKT GmbH & Co.KG

Product Name MKT Injection Mortar VME

Det	Detailed Rating												
Z	Description of the second	Monifertirer	Mass per	_	VOC-	Flooring	Composite	Recycled Content	Content	Regional Materials	/aterials	Rapidly	Certified
2			[%]	J	g/l	Systems	product	Post- Consumer	Pre- Consumer	Location Harvesting/ Extraction	Location Manufacturing	Material	Wood
F4	MKT Injection Mortar VME	MKT GmbH & Co.KG	~ 100%	37	420	N/A	N/A	Not specified	Not specified	Not specified	Not specified	N/A	A/N
A2													
A3													
<b>A4</b>													
A5													
A6													
A7													
A8													
98													
A10													
	MKT Injektionsmörtel VME	MKT Injektionsmörtel VME	100.0	<b>&gt;</b>		0	0	1	1	If the location of 'Harvesting & Extraction' and 'Manufacturing' is within a radius of 500 miles of the project the subproduct contributes to the credit.	& Extraction' and dius of 500 miles of the butes to the credit.	0	0
*  *	alues are based on the un	*All values are based on the unit: **LEED default recycled content for steel	led content fo	or steel									



Manufacturer MKT GmbH & Co.KG

Product Name MKT Injection Mortar VME

# IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants (1 Point)

#### Intent

Reduce the quantity of indoor air contaminants that are odorous, irritating and/or harmful to the comfort and well-being of installers and occupants caused by adhesives and sealants applied on site.

#### Requirement

All adhesive, sealants and sealant primers used on the interior of the building (defined as inside of the weatherproofing system and applied on-site) must comply shall comply with the VOC content limits of the following:

- SCAQMD Rule #1168 (effective date of July 1, 2005 and rule amendment date of January 7, 2005),
- Aerosol Adhesives must comply with Green Seal Standard for Commercial Adhesives GS-36 requirements in effect on October 19, 2000.

## IEQ Credit 4.2: Low Emitting Materials: Paints and Coatings (1 Point)

#### Inten

Reduce the quantity of indoor air contaminants that are odorous, irritating and/or harmful to the comfort and well-being of installers and occupants caused by paints and coatings applied on site.

#### Requirement

Paints and coatings used on the interior of the building (defined as inside of the weatherproofing system and applied on-site) must comply with the VOC content limits of the following:

- Green Seal Standard GS-11, Paints Edition, May 20, 1993,
- Green Seal Standard GC-03, Anti-Corrosive Paints, Second Edition, January 7, 1997, and
- South Coast Air Quality Management District (SCAQMD) Rule 1113, Architectural Coatings, rules in effect on January 1, 2004.

## **Detailed Rating**

No	Product Name	Manufacturer	Related	Product Type	VOC-C	ontent	Contribution of Product	
			Credit		Allowable	Product		
A1	MKT Injection Mortar VME	MKT GmbH & Co.KG	IEQ Credit 4.1	Other Adhesives (SCAQMD Rule 1168)	420g/l	<37g/l	The product fulfills the requirements for adhesives & sealants.	<b>✓</b>



Manufacturer MKT GmbH & Co.KG

Product Name MKT Injection Mortar VME

# MR Credit 4: Recycled Content (1-2 Points)

#### Intent

To increase demand for building products that incorporate recycled content materials, thereby reducing impacts resulting from extraction and processing of virgin materials.

#### Requirement

Use materials with recycled content\* such that the sum of post-consumer\*\* recycled content plus one-half of the pre-consumer\*\*\* content constitutes at least 10%/20% (based on cost) of the total value of the materials in the project.

The minimum percentage materials recycled for each point threshold is as follows:

- 10% Recycled Content -> 1 Point
- 20% Recycled Content -> 2 Points.
- \* Recycled content is defined in accordance with the International Organization of Standards document, ISO 14021 Environmental labels and declarations Self-declared environmental claims (Type II environmental labeling).
- \*\* Postconsumer material is defined as waste material generated by households or by commercial, industrial and institutional facilities in their role as end-users of the product, which can no longer be used for its intended purpose.
- \*\*\* Preconsumer material is defined as material diverted from the waste stream during the manufacturing process. Reutilization of materials (i.e., rework, regrind or scrap generated in a process and capable of being reclaimed within the same process that generated it) is excluded.

#### **Detailed Rating**

No	Product Name	Manufacturer	Recycled Post- Consumer	Content Pre- Consumer	Contribution of Product	
A1	MKT Injection Mortar VME	MKT GmbH & Co.KG	Not specified	Not specified	No recycled content specified.	_

Manufacturer MKT GmbH & Co.KG

Product Name MKT Injection Mortar VME

## MR Credit 5: Regional Materials (1-2 Points)

#### Intent

To increase demand for building materials and products that are extracted and manufactured within the region, thereby supporting the use of indigenous resources and reducing the environmental impacts resulting from transportation.

#### Requirement

Use building materials or products that have been extracted, harvested or recovered, as well as manufactured, within 500 miles of the project site for a minimum of 10% or 20%, based on cost, of the total materials value. If only a fraction of a product or material is extracted, harvested, or recovered and manufactured locally, then only that percentage (by weight) must contribute to the regional value. The minimum percentage regional materials for each point threshold is as follows:

- 10% Regional Materials -> 1 Point
- 20% Regional Materials -> 2 Points.

## **Detailed Rating**

No	Product Name	Manufacturer	Location Harvesting/ Extraction	Location Manufacturing
41	MKT Injection Mortar VME	MKT GmbH & Co.KG	Not specified	Not specified